

RT2100 Blue Wolf Diesel Compressor



RT2100 Blue Wolf compressor 21m³/min ATEX & DNV 2.7-1 is designed and built for offshore use. The compressor is diesel fueled and approved for ATEX Zone 2 and Norsok Z-015.

- **Approved for use without flame trap**
- **Low noise**
- **Duplex solution = twice as long service interval**
- **Exhaust can be prolonged with up to 40 m**
- **Siemens PLC operating and safety monitoring**
- **4 optional air outlets**
- **GPS Tracking**
- **HP air filtering for optimal HP air quality**

Technical data

Size (L x W x H):	4600 x 2300 x 2700 mm	Maximum Pressure:	10 Bar
ATEX Classification:	Zone 2	Start Air. Supply min.:	6 Bar
Chassis Type:	DNV 2.7-1 - 15' container	Hose Connection:	3 x 2" BSP + 1 x 1" CEJN
Unit Weight:	10500 kg	dB(A):	83 dB (A)
Load/m ² :	993 kg/m ²	Starter System:	Hydraulic starter
Plug Type:	CEAG 230/16 3P	Diesel Capacity:	400 L
Power Supply (V):	110-230 V	Fuel Consumption Max:	40 l/hour
Current (A):	3,0 A	Airflow:	21 m ³ /min

Equipment view



RT2100 Blue Wolf – superior safety standard, efficiency and reliability.

Contact us for your specific requirements.